

# Eaton 9395X UPS

600-2400 kW

Easy-deployment. Compact.  
Efficient. Reliable.



For over a decade, Eaton's 9395 UPS family has provided proven power protection with innovative technology. The latest addition of Eaton's 9395X UPS sets new market leading capabilities to manage growing data consumption demands today and in the future.

## Compact design

- Market leading power density, providing the best kW per square foot, leaving more space for revenue generating IT equipment
- Improved room configuration layout as stand-alone UPS or switchgear integrated system
- Prefabricated power solutions allow for improved room layout and system footprint

## Rapid system deployment

- World class manufacturing processes to allow shortest lead-time from order entry to commissioning
- Self-diagnostic software and tighter integration with service tools minimize onsite commissioning
- Eliminates the cost of load bank rentals and minimizes burn-in testing energy costs with the Easy Capacity Test

## Best uptime and reliability

- Highest energy efficient UPS to date
  - 99 percent efficient with Energy Saver System (ESS)
  - up to 97.5 percent efficiency in double-conversion mode
- EnergyAware native capabilities support the energy transition
- Multiple internal sensors with higher computing power to provide early warning capabilities and improve condition-based maintenance
- Handles up to 0.7 leading or lagging load power factors without de-rating UPS capacity
- HotSync patented load-sharing technology enables parallel operating of static converters without communication for sync or loadshare signals
- Global network of over 2,000 support and service personnel

## Efficiency and compatibility

Energy saver system <b>99%</b> efficiency	Lithium-ion compatible 	Double conversion <b>97.5%</b> efficiency
---	---	---

## ESS: How is it different than Eco mode?

- **Instantaneous action:** Less than two milliseconds transition time makes the UPS reaction time invisible to IT loads
- **Inherent surge suppression:** ESS provides transient suppression within the UPS—loads are protected from lightning events, even in ESS
- **Fault discrimination:** In a short circuit condition, the UPS detects the location of a fault (upstream or downstream), and reacts appropriately and instantly to protect the critical load



Powering Business Worldwide

# Technical specifications:

## UPS rating (unity power factor 1.0)

kW/kVA	600-2400 kW
--------	-------------

## General characteristics

Efficiency	99% in Energy Saver System (ESS) (up to 97.5% efficiency in double-conversion)
Parallel capability	4 UPS units maximum for distributed bypass
Ambient temperature	40 degree C (104 degree F)
Altitude (max)	1000m at 40 degree C (104 degree F)

## Input characteristics

Voltage	480V 3-wire, 400 V 4-wire
Voltage range	+10% / -15%
Frequency range	45–65 Hz
Power factor	0.99 for output loads greater than 60%
Input current distortion	<3% (no input filter required)
Soft start capability	Yes

## Output characteristics

Voltage	480V 3-wire, 400 V 4-wire
Regulation	±1%
Inverter	PWM
Voltage THD	<1% (100% linear load); <5% (non-linear load)
Load power factor range	Up to a 0.7 power factor leading/lagging without derating Up to a 0.5 power factor lagging with derating
Overload	110% for 10 min; 125% for 120 sec; 150% for 15 sec; >150% for 300 msec (UPS transfer to Bypass after OL time expires)

## Battery

Battery types	VRLA, AGM, wet cell, lithium-ion, supercapacitors
Battery voltage	480V
Charging method	ABM technology or float, selectable

## General characteristics

Control panel	Color Touchscreen interface
Battery startup	Standard
Frequency conversion	Standard
Multi-language	Standard
Building alarm inputs	5 (galvanic isolated)
Individual fan fail monitoring	Included
Power Semiconductor Temperature Monitoring	Included

## Options

External maintenance bypass	
PDU, RPP and STS	
DC disconnects	

## Remote or on-premises monitoring and management service

Eaton 9395X offers a 24x7 remote monitoring and predictive analytics subscription service to forecast data center power component failure and proactively replace components before failure.

## Communications

Direct battery monitoring via Modbus TCP/IP from UPS ethernet port
Software compatibility: Software and Power Xpert Reporting

The PXG-MS connectivity card can be installed at any time for the following protocols:

- Modbus TCP
- BACnet/WS
- BACnet/IP
- SNMP v.1, v.3, IPv6

Additional cards include:

- Industrial Relay card
- Environmental Monitoring Probe

Compliance with standards and directives:

- UL1778, cUL
- IEC 62040-1
- IEC 62040-2
- IEC 62040-3
- EU directive 2015/863/EU
- EU directive 2012/19/EU

1. Due to continuing improvements, specifications are subject to change without notice.